

konport.pl tasmy@konport.pl

Updated



Scotchâ Tape 8915 Performance Filament Tape

3M

Physical Properties Not for specification purposes

Manufactured in an ISO 9002 certified facility

Product Description	A high performance transparent tape reinforced along its length with continuous glass yarn filaments which give the tape high tensile strength.	The transparent ScotchPro™ backing provides stiffness and excellent abrasion, moisture and scuff resistance. The pressure sensitive	adhesive is specifically formulated to provide high adhesion, clean removability and stain resistance on most finishes.
	5		

Adhesive Type	Pressure sensitive hot melt solvent free (synthetic rubber resin)		
Backing	ScotchPro™ polypropylene film		
Reinforcement	Glass Yarn		
Thickness	150 microns (0.15 mm)	ASTM D-3652	
Colour	Transparent; blue		
Available Widths	Contact your local sales office	Available Lengths Contact your local sales office	
Core Size (ID)	76 mm (3")		
Storage Conditions	Store behind present stock, in a clean dry place. Temperature of 40 - 80°F (4-26°C) & 40-50 % Relative Humidity are recommended. Rotate your stock.		

Performance Characteristics Not for specification purposes	Adhesion to Stainless Steel	6.5 N/cm	ASTM D-3330
	Tensile Strength	298 N/cm	ASTM D-3759
	Elongation at Break	3 %	ASTM D-3759

Supersedes	: February 1999			
adhesive is specifically				

: June 2000

Date : June 2000 8915 Performance Filament Tape 2

3M, Scotch and ScotchPro are trademarks of the 3M Company.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications.

This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.

3M

Packaging Systems Division

3M ITALIA S.p.A. Packaging Systems Customer Service Via S. Bovio 3 - Milano S. Felice 20090 SEGRATE MI ITALY Tel. + 39 02 7035 3174/3173 Fax. + 39 02 7035 2104/3124 © 3M United Kingdom PLC 2000