



Double-Sided Adhesive Tape 9191

Product Data Sheet

Date: April 2018
Supersedes: April 2017

Product Description

3M™ Double-Sided Tape 9191 has a robust adhesive tape construction and a versatile use as mounting tape

Key Features

- universal carpet bonding tape with high tack and high adhesion on both sides
- suitable for fixation of various carpet floors and carpet tiles
- mounting aid for fixation, bonding or splicing of several substrates like plastic, metal, paper, cardboard, textiles, etc.
- suitable for rough and structured surfaces.
- hand-tearable

Physical Properties

Adhesive Type	Synthetic Rubber Resin
Thickness [mm] Tape without liner (PSTC 133)	0.230
Carrier	PET fabric
Release Liner	Brown double-sided siliconized paper
Thickness Liner [mm] (PSTC-133)	0.060
Tape Colour	white

Performance Characteristics

Adhesion to Stainless Steel [N/100 mm] (PSTC 101)	95
Tensile Strength, MD [N/25mm] (PSTC-131)	65
Elongation at Break [%] (PSTC-131)	9
Temperature Performance [°C] (SAFT, 0.5 °C /min, 250g/ 1"x1")	60
Short term temperature resistance:	75 °C (up to 1-hour max.)
Low temperature resistance:	-30 °C

Storage & Shelf Life

Store at 16 °C – 25 °C and 40-65 % relative humidity in its original box. The product can be stored up to 12 months after production.

Note: The shelf life may be shortened if the original packaging is not properly sealed or stored in an environment with high temperatures or light exposure.

Precautionary Information

3M has not prepared a MSDS for these products which are not subject to the MSDS requirements of the Occupational Safety and Health Administration's Hazard Communication Standard, 29 C.F.R. 1910.1200(b)(6)(v).

For information please contact your local 3M Office.

www.3M.com

For Additional Information

To request additional product information or to arrange for sales assistance, call.....

Address correspondence to: 3M

Important Notice

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

3M is a trademark the 3M Company.

Insert Company Information Before Issue